

## AT 316 - Fiche de données



### Description

AT 316 est adapté pour les tracteurs utilitaires compacts des services municipaux de voirie. Le dessin particulier de la bande de roulement assure une excellente traction sans compromettre la protection du champ – ce qui est essentiel pour ce type d'application. Le pneu AT 316 est aussi disponible en version "aramid belted", avec des ceintures en aramide qui permettent une meilleure résistance aux perforations.

### UM

International Standard

### Construction

BIAS

### Machinery

Agriculture: Tracteur compact

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
24 X 12.00 - 12	ARAMID BELTED	6	10.50 I - 55 ; I - 70 ; I - 90		315	610	271	1769	TL	
24 X 12.00 - 12	STANDARD	4	10.50 I - 55 ; I - 70 ; I - 90		315	610	271	1769	TL	E11-106R-004082

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 10:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..