

AT 603 - Spécifications techniques



Description

AT 603 est un pneu agro-industriel pour les outils agricoles et les chargeuses-pelleteuses. AT 603 a été conçu pour assurer une durabilité supérieure et une excellente traction sur la roue motrice et donc de très bonnes performances sur toutes les surfaces même que des qualités d'autonettoyage extraordinaires. Le pneu AT 603 est disponible en version "spécial" avec une carcasse renforcée, tandis que en la version "HD" qui offre une meilleure résistance aux coupures et déchirures.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Chargeuse-pelleteuse • Outillage agricole
Industriel: Chargeuse-pelleteuse

Version	STANDARD
Type	TL
Tyre Size	12.5/80 - 18
LI/SS DRIVE WHEEL	138 A8
LI/SS FREE ROLLING	150 A8

Dimensions International Standard

Ply Rating	18
Section Width (mm)	308
Overall Diameter (mm)	1000
Static Loaded Radius (mm)	448
Rolling Circumference (mm)	3027
SRI (mm)	475
Rim Rec	W 9
Rim Alt	11
ECE	E11-106R-004352

Load capacity (Kg)

	km/h / bar	5.50
	10 FR	4690
	25 FR	3985
	30 FR	3750
	40 FR	3350
	10 DW	3305
	25 DW	2810
	30 DW	2645
	40 DW	2360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 04:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..