

AW 702 IND - Fiche de données



Description

AW 702 IND a été conçu pour les applications industrielles. Ce pneu pour opérations pénibles a été développé par BKT pour offrir un nouveau degré de durabilité.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Remorque

SIZE	Version	USACode	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
6.00 - 16	INDUSTRIAL	94054206	103 A8	8	4.00 E	4.50 E ; 4½ K	6.7	28.4	13.3	84.6	TT	E11-106R-004358

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..