

## AW 702 - Spécifications techniques



### Description

AW 702 a été conçu pour les outils agricoles, les remorques et les presses à paille dans les applications de travail de la terre et de transport. Ce pneu pour opérations pénibles a été développé par BKT pour offrir un nouveau degré de durabilité. AW 702 est disponible en différentes versions pour répondre aux exigences spécifiques des utilisateurs : une version « aramid belted » avec ceintures en aramide pour garantir une résistance exceptionnelle aux crevaisons, une version « HD » avec un mélange particulièrement résistant aux coupures et déchirures et une version « special » particulièrement résistant aux chaumes.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Presse à paille • Outillage agricole • Remorque  
Industriel: Remorque

Version	STANDARD
Type	TL
Tyre Size	10.0/80 - 12
LI/SS FREE ROLLING	116 A8

## Dimensions International Standard

<b>Ply Rating</b>	8
<b>Section Width (mm)</b>	264
<b>Overall Diameter (mm)</b>	710
<b>Static Loaded Radius (mm)</b>	317
<b>Rolling Circumference (mm)</b>	2144
<b>Rim Rec</b>	9.00
<b>Rim Alt</b>	7.0

## Load capacity (Kg)

	km/h / bar	3.10
	10 FR	1750
	25 FR	1490
	30 FR	1400
	40 FR	1250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 00:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..