

AW 705 - Spécifications techniques



Description

AW 705 a été conçu pour les outils agricoles et remorques dans les applications de travail de la terre et de transport. Il convient pour être utilisé dans l'agriculture moderne grâce à une durabilité supérieure et une capacité de charge élevée.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Presse à paille • Outillage agricole • Remorque

Version	STANDARD
Type	TT
Tyre Size	14.0/65 - 16
LI/SS FREE ROLLING	134 A8

Dimensions US Standard

Usa code	94009909
Ply Rating	10
Section Width (inch)	13.9
Overall Diameter (inch)	34.3
Static Loaded Radius (inch)	15.3
Rolling Circumference (inch)	100.4
Rim Rec	11.0

Load capacity (lbs)

mph / psi	41
5 FR	6550
15 FR	5370
20 FR	5240
25 FR	4670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 17:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..