

AW 708 - Fiche de données

Description

AW 708 a été conçu pour le travail de la terre et les applications de transport et récolte du foin avec les outils agricoles, remorques et presses à paille. Une version « HD » est disponible avec un mélange particulièrement résistant aux coupures et déchirures.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Presse à paille • Outillage agricole • Remorque
Industriel: Remorque



SIZE	Version	USACode	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
400/60 - 15.5	HD	94052172	149 A8	18	AG 13.00		15.9	34.4	15	100.9	TL	E11-106R-004253
400/60 - 15.5	SPECIAL	94051250	149 A8	18	AG 13.00		15.9	34.4	15	100.9	TT	E11-106R-004255
400/60 - 15.5	SPECIAL	94048366	149 A8	18	AG 13.00		15.9	34.4	15	100.9	TL	
400/60 - 15.5	STANDARD	94010271	136 A8	10	AG 13.00		15.9	34.4	15	100.9	TL	E11-106R-003514
400/60 - 15.5	STANDARD	94010301	145 A8	14	AG 13.00		15.9	34.4	15	100.9	TT	E4-106R-002712
400/60 - 15.5	STANDARD	94010318	145 A8	14	AG 13.00		15.9	34.4	15	100.9	TL	E4-106R-002712
400/60 - 15.5	STANDARD	94010356	149 A8	18	AG 13.00		15.9	34.4	15	100.9	TL	E4-106R-001543
400/60 - 15.5	STUBBLE RESISTANT	94059560	149 A8	18	AG 13.00		15.9	34.4	15	100.9	TL	
19.0/45 - 17	STANDARD	94010233	138 A8	10	16.00		18.5	34.1	15	99.8	TL	E4-106R-002334
19.0/45 - 17	STANDARD	94010240	144 A8	14	16.00		18.5	34.1	15	99.8	TL	E4-106R-001883
19.0/45 - 17	STANDARD	94010257	148 A8	18	16.00		18.5	34.1	15	99.8	TL	E4-106R-002268
19.0/45 - 17	STUBBLE RESISTANT	94047697	152 A8	22	16.00		18.5	34.1	15	99.8	TL	E11-106R-003636
500/50 - 17	STANDARD	94010363	140 A8	10	16.00		19.7	37.2	16.4	108.3	TL	E4-106R-001884
500/50 - 17	STANDARD	94010370	149 A8	14	16.00		19.7	37.2	16.4	108.3	TL	E4-106R-001813
500/50 - 17	STANDARD	94030996	152 A8	16	16.00		19.7	37.2	16.4	108.3	TL	
500/50 - 17	STANDARD	94010387	154 A8	18	16.00		19.7	37.2	16.4	108.3	TL	E4-106R-002269
500/65 - 17	STANDARD	94034307	160 A8	18	16.0		20.7	42.5	18.2	123.4	TL	E11-106R-004549
520/50 - 17	STANDARD	94063413	162 A8		16.00		20.3	37.5	15.9	109.3	TL	E11-106R-005852

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 17:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..