

AW 729 - Spécifications techniques



Description

L'AW 729 est un pneu agricole spécialement conçu pour le transport, la récolte du foin, le bottelage et le travail des sols. Son épaulement arrondi et la conception de sa bande de roulement à trois rainures centrales assurent un faible compactage du sol et évitent les dégâts causés au champ. L'AW 729 est le pneu idéal pour l'agriculture moderne. Il est adapté pour une utilisation aussi bien sur route que hors route.

UM

US Standard

Construction

✚ BIAS

Machinery

Agriculture: Presse à paille • Outillage agricole • Remorque

Version	STANDARD
Type	TL
Tyre Size	340/55 - 16 (13.0/55 - 16)
LI/SS DRIVE WHEEL	121 A8
LI/SS FREE ROLLING	133 A8

Dimensions US Standard

Usa code	94066117
Section Width (inch)	13.5
Overall Diameter (inch)	30.9
Static Loaded Radius (inch)	14.1
Rolling Circumference (inch)	92.8
Rim Rec	11.0
ECE	E11-106R-006421

Load capacity (lbs)

mph / psi	46
5 FR	6360
15 FR	5400
20 FR	5080
25 FR	4540
5 DW	4475
15 DW	3805
20 DW	3580
25 DW	3200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..