

BK 4040 - Spécifications techniques



Description

BK 4040 a été conçu essentiellement pour les remorques dans les applications de transport. La carcasse robuste lui confère une capacité de charge élevée et une durabilité supérieure.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Remorque

Version	STANDARD
Type	TT
Tyre Size	6.50 - 16

Dimensions International Standard

Ply Rating	10
Section Width (mm)	182
Overall Diameter (mm)	740
Rim Rec	4.50 E
ECE	E11-106R-005299

Load capacity (Kg)

km/h / bar	4.10
30	1010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 00:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..