

BK 6060 - Spécifications techniques



Description

BK 6060 est un pneu qui convient tant aux champs que sur la route, il a été conçu pour les remorques et les chargeuses-pelleteuses dans les applications de transport et pour les opérations d'excavation et chargement. Le dessin à blocs de sa bande de transport lui garantit un cycle de vie plus long.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Chargeuse-pelleteuse • Remorque

Version	INDUSTRIAL
Type	TT
Tyre Size	9.00 - 16

Dimensions US Standard

Usa code	94027323
Ply Rating	16
Section Width (inch)	10
Overall Diameter (inch)	36.4
Static Loaded Radius (inch)	16.8
Rolling Circumference (inch)	107.9
Rim Rec	6.50 H
Rim Alt	6.00 G
ECE	E11-106R-004362

Load capacity (lbs)

mph / psi	105
20	5070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..