

BK 627 - Fiche de données



Description

BK 627 est un pneu dont le dessin de la bande de roulement est à blocs, il convient pour les opérations de transport et travail de la terre avec des tracteurs et outils agricoles. Il est essentiellement destiné à une utilisation aux champs et il est idéal pour les opérations pénibles.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole • Tracteur • Remorque

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
7.50 - 16	STANDARD	94041183	121 A8	12	6.0		8.7	31.9	14.4	98.2	TT	E11-106R-004256

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 10:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..