

## BK 823 - Fiche de données



### Description

BK 823 est un pneu essentiellement conçu pour les tracteurs, outils agricoles et remorques dans les applications de transport et travail de la terre. Le dessin spécial à blocs de sa bande de roulement fait qu'il est particulièrement adapté pour les opérations pénibles en offrant une excellente performance de direction. Une version HD, qui assure une résistance avancée aux coupures et déchirures, est aussi disponible.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Outillage agricole • Tracteur • Remorque

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
9.00 - 16	HD	94049202	127 A8	14	6.5		9.6	35.1	15.5	101.7	TT	E11-106R-004338
9.00 - 16	STANDARD	94042432	124 A8	12	6.5		9.6	35.1	15.5	101.7	TT	E11-106R-003603
9.00 - 16	STANDARD	94040131	127 A8	14	6.5		9.6	35.1	15.5	101.7	TT	E11-106R-003604
9.00 - 16	STANDARD	94060252	121 A8	10	6.5		9.6	35.1	15.5	101.7	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 12:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..