

BK 826 - Spécifications techniques



Description

Le pneu BK 826 est conçu par des experts pour les remorques dans les applications de transport, offrant une durabilité et des performances inégalées. La version « Harvester Special » est spécialement conçue pour la récolte et garantit une fiabilité optimale sur le terrain. Ce pneu diagonal est doté d'une carcasse renforcée, offrant une capacité de charge exceptionnelle pour répondre aux exigences des tâches lourdes. De plus, la BK 826 est disponible dans une variante « industrielle », conçue avec une résistance supérieure aux coupures et aux éclats, ce qui en fait un choix idéal pour les chargeuses-pelleteuses dans des conditions difficiles.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Moissonneuse • Remorque
Industriel: Chargeuse-pelleteuse • Remorque

| | |
|-----------|-----------------|
| Version | TRACTOR TRAILER |
| Type | TT |
| Tyre Size | 8.25 - 16 |
| LI/SS | 134 A8 |

Dimensions US Standard

| | |
|-------------------------|----------|
| Usa code | 94045518 |
| Ply Rating | 16 |
| Section Width (inch) | 9.4 |
| Overall Diameter (inch) | 34 |
| Rim Rec | 6.50 H |
| Rim Alt | 6.00 G |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 110 |
| 25 | 4680 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 04:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..