

## BK-LOADER 53 - Spécifications techniques



### Description

BK-LOADER 53 est un pneu avec ceintures en aramide, développé pour les chargeurs dans les applications industrielles. Le dessin exclusif de la bande de roulement extra-profonde garantit une excellente stabilité latérale ainsi qu'une extraordinaire résistance à l'usure, aux coupures et aux crevaisons. BK-LOADER 53 se distingue par d'exceptionnelles propriétés d'autonettoyage, et par une traction et une adhérence optimales sur surfaces mouillées et sèches. Ce pneu est particulièrement adapté pour les opérations de recyclage.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Industriel: Chargeur

Version	ARAMID BELTED
Type	TL
Tyre Size	405/70 R 20
LI/SS	155A2/151A4

## Dimensions International Standard

Section Width (mm)	407
Overall Diameter (mm)	1097
Static Loaded Radius (mm)	511
Rolling Circumference (mm)	3339
SRI (mm)	525
Rim Rec	13
Rim Alt	14 ; 13 SDC; 12 ;12 SDC

## Load capacity (Kg)

km/h / bar	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5
20 TRANSPORT	1210	1520	1805	2090	2375	2640	2905	3170	3450
10 LOADING	1375	1725	2050	2375	2700	3000	3300	3600	3875
Static	2200	2750	3275	3800	4325	4800	5300	5750	6200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13/03/2025 20:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..