

COMMANDER TWIN RIB - Spécifications techniques



Description

COMMANDER TWIN RIB est un pneu avec nervure de la bande de roulement à 4 côtes et dentelures sur les épaules pour offrir une excellente adhérence. Le profil plus large de la bande de roulement garantit une parfaite répartition du poids. La carcasse robuste et le mélange supérieur de la bande de roulement assurent une longue vie du pneu. COMMANDER TWIN RIB est idéal pour les applications de travail de la terre et de transport.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur 2WD

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16
LI/SS	103 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	210
Overall Diameter (mm)	810
Rim Rec	5.50 F
Rim Alt	5.00 F ; 5 K ; 6.00 F
ECE	E11-106R-006953
TRA Code	F2

Load capacity (Kg)

km/h / bar	3.70
30	875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..