

CON STAR - Spécifications techniques



Description

CON STAR est particulièrement adapté pour les chargeuses compactes et chargeuses télescopiques dans les applications agro-industrielles de levage et de chargement. Ce pneu est caractérisé par une traction exceptionnelle associée à une excellente stabilité verticale et horizontale. CON STAR a été réalisé dans un mélange particulièrement résistant à tous les types de coupure qui contribue à allonger le cycle de vie du pneu.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Chargeuse compacte • Chargeuse télescopique

Industriel: Chargeuse compacte • Chargeuse télescopique

| | |
|-----------|----------------------------|
| Version | INDUSTRIAL |
| Type | TL |
| Tyre Size | 440/80 - 28 (16.9 - 28) |
| LI/SS | 156 A8 |

Dimensions US Standard

| | |
|------------------------------|---------------------------|
| Usa code | 94051199 |
| Section Width (inch) | 17.7 |
| Overall Diameter (inch) | 55.9 |
| Static Loaded Radius (inch) | 24.9 |
| Rolling Circumference (inch) | 169.3 |
| Rim Rec | DW 14 L |
| Rim Alt | DW 13 ; DW 13 L ; DW 15 L |
| ECE | E11-106R-003035 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 46 |
| 25 | 8820 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 00:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..