

DON 2000 - Spécifications techniques



Description

DON 2000 est un pneu adapté pour les opérations de transport avec remorques et camionnettes tant sur route que hors route. Il assure une durabilité exceptionnelle ainsi que des performances élevées pendant tout le cycle de vie du produit.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Camion léger • Remorque

Version	TRACTOR TRAILER
Type	TT
Tyre Size	9.00 - 20

Dimensions International Standard

Ply Rating	16
Section Width (mm)	270
Overall Diameter (mm)	1048
Rim Rec	7.0
Rim Alt	6.5 ; 7.5

Load capacity (Kg)

km/h / bar	7.25
40	2715

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 00:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..