

EARTHMAX CRUSHER HAUL - Spécifications techniques



Description

EARTHMAX CRUSHER HAUL est un pneu radial All Steel conçu pour les applications de transport sur route que hors route, ainsi que les opérations dans les mines. Le pneu offre une plus grande durabilité et un kilométrage supérieur. La robuste construction et carcasse avec des ceintures d'acier garantit un capacité de charge élevée. Le dessin de la bande de roulement à blocs assure une excellente traction. En route, EARTHMAX CRUSHER HAUL offre un confort de conduit extraordinaire, un niveau de manœuvrabilité élevé, ainsi que moins de fatigue pour le conducteur.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Camion à benne basculante

Version	STANDARD
Type	TT
Tyre Size	11.00 R 20
LI/SS	152/149 J

Dimensions International Standard

Ply Rating	18
Overall Width (mm)	290
Overall Diameter (mm)	1102
Rim Rec	8.00
Rim Alt	8.50

Load capacity (Kg)

	km/h / bar	8.30
100 Load Single		3550
100 Load Dual		3250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 17:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..