

EARTHMAX SR 22 - Spécifications techniques



Description

EARTHMAX SR 22 (G-2/L-2) est un pneu radial **All Steel** (Tout Acier) particulièrement conçu pour les niveleuses et chargeuses qui opèrent l'hiver dans des conditions extrêmes sur la neige ou la glace. Les opérateurs en apprécieront l'excellente traction et l'extraordinaire stabilité assurées par le dessin de la bande de roulement large et non-directionnel.

UM

US Standard

Construction

 RADIAL

Machinery

Industriel: Bulldozer • Niveleuse • Chargeur

OTR: Bulldozer • Niveleuse • Chargeur

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 14.00 R 24 |
| LI/SS | 153 A8/175 A2 |

Dimensions US Standard

| | |
|------------------------------|--------------------|
| Usa code | 94048816 |
| Overall Width (inch) | 14.4 |
| Overall Diameter (inch) | 53.9 |
| Static Loaded Radius (inch) | 24.6 |
| Rolling Circumference (inch) | 163 |
| Rim Rec | 8.00 TG |
| Rim Alt | 9.00 GR , 10.00 VA |
| Star Rating | * |
| TRA Code | G2/L2 |

Load capacity (lbs)

| mph / psi | 29 | 33 | 36 | 40 | 44 | 47 | 51 | 54 | 76 | 80 |
|-----------|------|------|------|------|------|------|------|------|-------|-------|
| 25 | 4940 | 5360 | 5840 | 6150 | 6600 | 7150 | 7400 | 8050 | - | - |
| 5 | - | - | - | - | - | - | - | - | 14800 | 15200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 14:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..