

## EARTHMAX SR 30 - Spécifications techniques



### Description

EARTHMAX SR 30 (E-3/L-3) est un pneu radial **All Steel** (Tout Acier) conçu pour une double utilisation avec chargeuses ou tombereaux rigides. Les ceintures d'acier multicouches et le dessin rigide à blocs assurent une traction, une stabilité et une durabilité excellentes. Le mélange spécial résistant aux coupures fait de EARTHMAX SR 30 la solution idéale pour un grand nombre de conditions opérationnelles difficiles.

### UM

International Standard

### Construction

RADIAL

### Machinery

OTR: Tombereau articulé • Bulldozer • Chargeur

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	208 A2

## Dimensions International Standard

Overall Width (mm)	765
Overall Diameter (mm)	1861
Static Loaded Radius (mm)	818
Rolling Circumference (mm)	5555
Rim Rec	25.00/3.5
Star Rating	*
TRA Code	L3

## Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00
10	15500	16000	17000	17500	18000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 14:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..