

## EARTHMAX SR 315 - Spécifications techniques



### Description

EARTHMAX SR 315 est un pneu radial tout en acier spécialement conçu pour les chargeurs-transporteurs. Il offre d'excellentes performances dans les opérations de creusement, de chargement, et de chargement et de transport dans les mines souterraines.

Il est équipé d'une carcasse robuste, renforcée par plusieurs courroies en acier qui minimisent la rupture par impact et les crevaisons dues aux cailloux. Les parois latérales et les contreforts renforcés de l'EARTHMAX SR 315 garantissent d'excellentes performances dans des conditions rocheuses sévères, minimisant les coupures de roche et les dommages causés par le frottement. Sa bande de roulement lisse L-3S réduit le perçage par des roches et des pierres.

Le composé EARTHMAX SR 315 est spécialement conçu pour assurer un faible dégagement de chaleur et une fiabilité dans les services miniers souterrains.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Chargeur-transporteur LHD

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 29
LI/SS	211 A2

## Dimensions International Standard

Overall Width (mm)	725
Overall Diameter (mm)	1865
Static Loaded Radius (mm)	830
Rolling Circumference (mm)	5635
Rim Rec	22.00/3.0
Star Rating	**
TRA Code	L3S

## Load capacity (Kg)

km/h / bar	5.25	5.50	5.75	6.00	6.25	6.50
10	16500	17500	18000	18500	19000	19500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 23:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..