



EARTHMAX SR 33 PLUS - Fiche de données



Description

EARTHMAX SR 33 PLUS est un pneu radial avec un dessin particulier à blocs multiples conçu pour assurer une excellente traction sur les surfaces molles, sablonneuses ou boueuses. La carcasse All Steel robuste avec les ceintures d'acier se distinguent de par une excellente durabilité et une grande résistance aux coupures et crevaisons. EARTHMAX SR 33 PLUS offre une excellente stabilité ainsi que des propriétés d'auto-nettoyage exceptionnelles.

UM

US Standard

Construction

RADIAL

Machinery

Industriel: Véhicule universel

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
16.00 R 20	STANDARD	94064038	173/170 G	11.25	10.00W, 10.0	17.6	51.6	22.9	156.5	TL	E11-54R-0017916

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..