

## EARTHMAX SR 42 - Spécifications techniques



### Description

EARTHMAX SR 42 est un pneu radial OTR particulièrement conçu pour les trains routiers dans les mines "haul train" et les applications lourdes pour le transport de bois. Le dessin caractéristique de la bande de roulement assure d'excellentes traction et stabilité latérale ainsi que des performances exceptionnelles de freinage et de comportement dans les virages sur terrains accidentés ou sur graviers même en présence de neige ou verglas. En effet, le mélange de la bande de roulement, particulièrement résistant aux coupures et à l'usure, est parfaitement adapté aux conditions climatiques extrêmement froides. EARTHMAX SR 42 présente une carcasse All Steel (Tout Acier) qui garantit une solidité exceptionnelle et un long cycle de vie.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Haul Train

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	14.00 R 24
LI/SS	171 B

## Dimensions International Standard

TKPH	105
Overall Width (mm)	380
Overall Diameter (mm)	1412
Static Loaded Radius (mm)	652
Rolling Circumference (mm)	4231
Rim Rec	10.00W
Rim Alt	--
Star Rating	***
TRA Code	E4

## Load capacity (Kg)

km/h / bar	7.00	8.00
50	5800	6150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..