

EARTHMAX SR 431 - Spécifications techniques



Description

EARTHMAX SR 431 (E-4) est un pneu radial All Steel particulièrement conçu pour les tombereaux rigides qui opèrent dans des conditions extrêmes, notamment dans les mines à ciel ouvert et souterraines. Le dessin non directionnel de la bande de roulement assure d'excellentes traction et stabilité. Ce pneu est caractérisé par une carcasse robuste All Steel et par un mélange spécial qui garantissent une résistance aux coupures et crevaisons ainsi que un cycle de vie plus long même dans les milieux rocheux, abrasifs et hostiles.

UM

US Standard

Construction

RADIAL

Machinery

OTR: Tombereau rigide

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	16.00 R 25
LI/SS	183 B

Dimensions US Standard

Usa code	94073603
TMPH	114
Overall Width (inch)	17.8
Overall Diameter (inch)	60.3
Static Loaded Radius (inch)	28.1
Rolling Circumference (inch)	183
Rim Rec	11.25/2.0
Star Rating	***
TRA Code	E4
Tread Depth	57

Load capacity (lbs)

mph / psi	109	116	123	131
30	16500	17600	18200	19300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/02/2025 09:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..