

## EARTHMAX SR 44 - Spécifications techniques



### Description

EARTHMAX SR 44 est un pneu radial **All Steel** (Tout Acier) adapté pour une série d'applications y compris les opérations dans les mines, les forêts ou de transport. Le dessin robuste de la bande de roulement E-4 assure une excellente traction et un grand confort pour l'opérateur. EARTHMAX SR 44 (E-4) est en mesure d'optimiser la productivité, quelle que soit votre opération.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Camion à benne basculante

Version	STANDARD
Type	TL
Tyre Size	325/95 R 24 (12.00 R 24)
LI/SS	158 B

## Dimensions International Standard

TKPH	140
Overall Width (mm)	310
Overall Diameter (mm)	1250
Static Loaded Radius (mm)	575
Rolling Circumference (mm)	3790
Rim Rec	8.50V
Rim Alt	9.00V
Star Rating	***
TRA Code	E4

## Load capacity (Kg)

km/h / bar	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	3075	3150	3350	3450	3550	3650	3750	3875	4000	4125	4250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 21:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..