

EARTHMAX SR 452 - Spécifications techniques



Description

EARTHMAX SR 452 est un pneu radial All Steel (Tout Acier) spécialement conçu pour les tombereaux articulés pour les opérations de transport. Le dessin unique de la bande de roulement d'une profondeur E-4, assure une excellente traction et une résistance particulière à la chaleur en offrant un niveau de vibrations et bruits réduit pour garantir confort et manœuvrabilité optimales. La carcasse et les ceintures All Steel assurent une excellente stabilité et une grande résistance aux coupures et crevaisons. EARTHMAX SR 452 est réalisé avec une épaulement en forme de carré qui assure un contact optimal avec le terrain et une manœuvrabilité exceptionnelle.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Tombereau rigide

Version	STANDARD COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	212 B

Dimensions US Standard

Usa code	94063987
TMPH	284
Overall Width (inch)	26
Overall Diameter (inch)	85.4
Static Loaded Radius (inch)	39.2
Rolling Circumference (inch)	264.9
Rim Rec	17.00/3.5
Star Rating	***
TRA Code	E4

Load capacity (lbs)

mph / psi	105	109	112	116
30	41900	42500	43000	44100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 23:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..