

EARTHMAX SR 47 TP - Fiche de données



Description

L'EARTHMAX SR 47 TP (E-4) est un pneu radial tout en acier spécialement conçu pour les camions de transport rigides opérant dans des conditions nécessitant une traction et une résistance à la crevaison maximales. La profondeur de la bande de roulement E-4 garantit une grande résistance à l'usure, même sur de longues distances, ce qui réduit les temps d'arrêt et augmente la productivité. EARTHMAX SR 47 TP est idéal pour toutes les tâches exigeant à la fois de la traction et de la stabilité, en particulier sur les terrains boueux ou glissants. Disponible en version standard et composés résistants aux coupures.

UM

US Standard

Construction



RADIAL

Machinery

OTR: Tombereau rigide

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
24.00 R 35	CUT RESISTANT COMPOUND	94074204	E4	**	209 B	17.00/3.5	--	26.4	86	38.8	260.8	TL	258
24.00 R 35	STANDARD COMPOUND	94074211	E4	**	209 B	17.00/3.5	--	26.4	86	38.8	260.8	TL	301

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..