

EARTHMAX SR 47 - Fiche de données



Description

EARTHMAX SR 47 (E-4) est un pneu radial **All Steel** (Tout Acier) particulièrement conçu pour les tombereaux rigides qui opèrent dans des conditions nécessitant la plus grande résistance aux coupures et perforations dans les milieux rocheux. Le dessin unique de la bande de roulement d'une profondeur E-4 réduit l'usure en assurant une vie plus longue du pneu même sur de longs parcours. Ceci se traduit par des temps d'arrêt machine réduits, ce qui augmente la productivité. Disponible avec mélange standard ou résistant aux coupures.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Tombereau rigide

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
18.00 R 33	CUT RESISTANT COMPOUND	E4	***	195 B	13.00/2.5		510	1885	867	5674	TL	168
18.00 R 33	CUT RESISTANT COMPOUND	E4	**	191 B	13.00/2.5	--	510	1885	867	5674	TL	168
18.00 R 33	HEAT RESISTANT	E4	**	191 B	13.00/2.5	--	510	1885	867	5674	TL	228
18.00 R 33	STANDARD COMPOUND	E4	***	195 B	13.00/2.5		510	1885	867	5674	TL	204
18.00 R 33	STANDARD COMPOUND	E4	**	191 B	13.00/2.5	--	510	1885	867	5674	TL	204
21.00 R 33	CUT RESISTANT COMPOUND	E4	**	200 B	15.00/3.0	--	575	2001	918	6113	TL	227
21.00 R 33	STANDARD COMPOUND	E4	**	200 B	15.00/3.0	--	575	2001	918	6113	TL	270
21.00 R 35	CUT RESISTANT COMPOUND	E4	**	201 B	15.00/3.0	17.00/3.0	585	2045	944	6313	TL	261
21.00 R 35	HEAT RESISTANT COMPOUND	E4	**	201 B	15.00/3.0	17.00/3.0	585	2045	944	6313	TL	355
21.00 R 35	STANDARD COMPOUND	E4	**	201 B	15.00/3.0	17.00/3.0	585	2045	944	6313	TL	305
24.00 R 35	CUT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5	--	670	2181	983	6565	TL	266
24.00 R 35	CUT RESISTANT COMPOUND	E4	***	212 B	17.00/3.5	--	670	2181	983	6565	TL	266
24.00 R 35	STANDARD COMPOUND	E4	**	209 B	17.00/3.5	--	670	2181	983	6565	TL	315
24.00 R 35	STANDARD COMPOUND	E4	***	212 B	17.00/3.5	--	670	2181	983	6565	TL	315

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..