

EARTHMAX SR 484 - Spécifications techniques



Description

L'EARTHMAX SR 484 PLUS est un pneu radial tout en acier spécialement conçu pour les camions à benne rigides destiné au transport en surface dans le secteur minier. Il est doté d'une conception de la bande de roulement unique E-3, avec un composé spécial qui assure une excellente protection sur des terrains difficiles et rocheux, ainsi qu'une traction accrue et d'excellentes propriétés d'auto-nettoyage. Sa construction tout acier avec des ceintures en acier multicouches offre une protection optimale contre les chocs, la fatigue et l'infiltration de roches, ce qui améliore le temps de disponibilité pour une productivité plus élevée. L'EARTHMAX SR 484 présente un épaulement en forme de carré, qui maximise le contact avec le sol pour une maniabilité et une stabilité optimales. Ce pneu BKT est spécialement conçu pour les vitesses plus élevées et les longs trajets.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Tombereau rigide

Version	STANDARD COMPOUND
Type	TL
Tyre Size	27.00 R 49
LI/SS	223 B

Dimensions US Standard

Usa code	94067831
TMPH	418
Overall Width (inch)	28.9
Overall Diameter (inch)	104.2
Static Loaded Radius (inch)	47
Rolling Circumference (inch)	317.1
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E3
Tread Depth	60

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	45400	48100	49400	50700	52000	55100	56800	58400	60000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/02/2025 15:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..