

EARTHMAX SR 49 M - Fiche de données



Description

Earthmax SR 49 M est un pneu radial All Steel (Tout Acier) avec un dessin non directionnel particulièrement conçu pour chargeurs-transporteurs (LHD), tombereaux surbaissés, chargeurs sur roues et bulldozers qui opèrent dans des conditions rocheuses extrêmes, notamment dans les mines souterraines. Earthmax SR 49 M est idéal pour les opérations difficiles qui demandent une traction exceptionnelle. La bande de roulement de profondeur L-4, associée au mélange avec formule spéciale UMS (underground mine service) lui assure une résistance supérieure à l'usure ainsi qu'une excellente résistance contre les coupures dues aux rochers et les crevaisons.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Bulldozer • Chargeur-transporteur LHD • Chargeur • Tombereau surbaissé

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
26.5 R 25	CUT RESISTANT COMPOUND	94058976	L4	**	209 A2	22.00/3.0		27.9	70.2	31.5	208.5	TL	0
26.5 R 25	CUT RESISTANT COMPOUND	94058983	E4/L4	**/*	193 B/202 A2	22.00/3.0		27.9	70.2	31.5	208.5	TL	113
26.5 R 25	CUT RESISTANT COMPOUND	94058969	L4	*	202 A2	22.00/3.0		27.9	70.2	31.5	208.5	TL	0
26.5 R 25	CUT RESISTANT COMPOUND	94067930	E4/L4	****/****		22.00/3.0		27.9	70.2	31.5	208.5	TL	0
26.5 R 25	CUT RESISTANT COMPOUND (UMS)	94058990	E4	****		22.00/3.0		27.9	70.2	31.5	208.5	TL	0
29.5 R 25	CUT RESISTANT COMPOUND	94058457	L4	*	208 A2	25.00/3.5		30.7	75	33.2	220.5	TL	0
29.5 R 25	CUT RESISTANT COMPOUND	94058440	L4	**	216 A2	25.00/3.5		30.7	75	33.2	220.5	TL	0
29.5 R 25	CUT RESISTANT COMPOUND	94058426	E4/L4	**/*	200 B/208 A2	25.00/3.5		30.7	75	33.2	220.5	TL	151
29.5 R 25	CUT RESISTANT COMPOUND	94067947	E4/L4	****/****		25.00/3.5		30.7	75	33.2	220.5	TL	0
29.5 R 25	CUT RESISTANT COMPOUND (UMS)	94058433	E4	****		25.00/3.5		30.7	75	33.2	220.5	TL	0
29.5 R 29	CUT RESISTANT COMPOUND	94052400	L4	***	223 A2	25.00/3.5	24.00/3.5,26.00/3.5	30.9	79	35.7	248.8	TL	0
29.5 R 29	CUT RESISTANT COMPOUND (UMS)	94058648	E4	****		25.00/3.5	24.00/3.5, 26.00/3.5	30.9	79	35.7	248.8	TL	0

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 06:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..