

## EARTHMAX SR 57 - Spécifications techniques



### Description

EARTHMAX SR 57 est un pneu radial All Steel (Tout Acier) particulièrement conçu pour les chargeurs, bulldozers et les véhicules utilitaires utilisées dans les mines souterraines. Ce pneu assure une traction supérieure, ainsi que stabilité et confort sur les terrains rugueux et rocheux. La bande de roulement extra profonde L-5, associée au mélange avec formule spéciale UMS (underground mine service), lui assure une résistance supérieure à l'usure ainsi qu'une excellente résistance contre les coupures dues aux rochers et les crevaisons.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Bulldozer • Chargeur-transporteur LHD • Chargeur

Version	CUT RESISTANT COMPOUND
Type	TT
Tyre Size	7.50 R 15

## Dimensions International Standard

Overall Width (mm)	223
Overall Diameter (mm)	845
Rim Rec	6.00
Rim Alt	6.5
Star Rating	*
TRA Code	L5

## Load capacity (Kg)

km/h / bar	7.00
6.00	2600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..