

EARTHMAX SR LOADER - Spécifications techniques



Description

EARTHMAX SR LOADER est un pneu OTR particulièrement conçu pour les opérations de chargement et nivellement, ainsi que pour les applications de transport avec tombereaux articulés. Sa carcasse All Steel (Tout Acier) renforcée par des ceintures en acier multicouche et le composé exclusif de la bande de roulement offrent une résistance exceptionnelle aux déchirures et crevaisons, ce qui se traduit par une durée de vie plus longue du pneu. EARTHMAX SR LOADER est doté d'un dessin exclusif de la bande de roulement qui assure d'excellentes propriétés d'auto-nettoyage et une traction optimale sur une large gamme de terrains.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Tombereau articulé • Bulldozer • Chargeur

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	20.5 R 25
LI/SS	177 B/186 A2

Dimensions US Standard

Usa code	94064250
TMPH	116
Overall Width (inch)	20.9
Overall Diameter (inch)	58.1
Static Loaded Radius (inch)	25.6
Rolling Circumference (inch)	172.6
Rim Rec	17.00/2.0
Star Rating	**/*
TRA Code	E3/L3

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	12800	13600	14300	14800	15200	16100
5	17600	18200	19300	19800	20900	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..