

EM 937 IND3 (ECH) - Spécifications techniques



Description

EM 937 (E-3) IND a été particulièrement conçu pour la manutention de conteneurs vides dans les applications de gerbage et chargement. Ce pneu se distingue de par une durabilité très élevée et donc une longue vie. EM 937 (E-3) IND est idéal pour les surfaces asphaltées et pour toutes les opérations qui exigent un niveau de manutention élevé dans les ports. *For size 14.00-24 please confirm service rim or consult manufacturer/distributor

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chariot porte-conteneurs vide

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	14.00 - 24

Dimensions International Standard

Ply Rating	28
Overall Width (mm)	375
Overall Diameter (mm)	1368
Static Loaded Radius (mm)	628
Rolling Circumference (mm)	4050
Rim Rec	10.00 WA
Rim Alt	10.00 VA
TRA Code	IND3

Load capacity (Kg)

km/h / bar	10.00
10	13500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 08:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..