

FARM 2000 - Spécifications techniques



Description

Le pneu FARM 2000 est adapté pour les tracteurs dans les applications de travail de la terre. Ce pneu a été conçu avec un mélange résistant aux coupures et déchirures, pour assurer une durabilité supérieure. Grâce à la carcasse particulièrement robuste, FARM 2000 garantit une capacité de charge élevée. Il assure aussi une excellente traction et des grandes propriétés d'auto-nettoyage.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TT
Tyre Size	16.9 - 28
LI/SS	139 A8

Dimensions US Standard

Usa code	94002924
Ply Rating	12
Section Width (inch)	16.9
Overall Diameter (inch)	55.9
Static Loaded Radius (inch)	25.9
Rolling Circumference (inch)	171.3
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-003627
TRA Code	R1

Load capacity (lbs)

	mph / psi	36
	25	5360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 14:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..