

## FL 252 - Spécifications techniques



### Description

FL 252 est un pneu adapté pour les applications de récolte du foin avec andaineurs rotatifs/faneuses ainsi que pour les opérations logistiques avec chariots élévateurs. Ce pneu garantit une excellente durabilité, tandis que le dessin spécial de la bande de roulement assure un maximum de stabilité pendant les opérations de levage.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Adaineur rotatif  
Industriel: Chariot élévateur

Version	STANDARD
Type	TT
Tyre Size	6.50 - 10

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	185
Overall Diameter (mm)	605
Rim Rec	5.00 F
Rim Alt	5.50 F

## Load capacity (Kg)

	km/h / bar	7.80
25 LOAD WHEEL		1950
25 STEER WHEEL		1500
10 OTHER VEHICLES		1950
25 OTHER VEHICLES		1500
STATIC SIDE LOADER		2265

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 23:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..