

FL 630 SUPER - Spécifications techniques



Description

FL 630 SUPER est un pneu Flotation particulièrement adapté pour les applications aux champs et sur route avec des remorques, camions-citernes et épandeurs. Sa structure résistante fournit une excellente traction et une adhérence parfaite même dans les virages et lors des manœuvres. Le dessin particulier de la bande de roulement garantit des propriétés de flottaison élevées en minimisant le compactage du sol en plus de propriétés d'autonettoyage exceptionnelles. FL 630 SUPER supporte des vitesses jusqu'à 70 km/h.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Épandeur • Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	850/50 R 30.5
LI/SS	182 D
LI/SS DRIVE WHEEL	182 D
LI/SS FREE ROLLING	182 D

Dimensions International Standard

Section Width (mm)	860
Overall Diameter (mm)	1625
Static Loaded Radius (mm)	722
Rolling Circumference (mm)	4895
SRI (mm)	775
Rim Rec	AG 28.00
ECE	E11-106R-008232

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	3175	3945	4490	5185	5880	6425	7040	7735
65	3485	4335	4930	5695	6460	7055	7735	8500
50	4220	5250	5970	6895	7820	8540	9360	10285
40	4740	5900	6705	7750	8790	9595	10520	11560
25	5510	6850	7790	9000	10210	11150	12225	13430
10	6275	7805	8875	10255	11630	12700	13925	15300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 21:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..