

## FLOTATION 648 - Spécifications techniques



### Description

FLOTATION 648 est particulièrement adapté pour les transports aux champs et sur la route et pour les applications avec épandeurs. Certaines tailles conviennent pour les moissonneuses/presses à balles de foin. Le dessin particulier de la bande de roulement permet le transport de charges très lourdes à de basses pressions, ce qui garantit un moindre compactage du sol tout en protégeant les cultures des dommages.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Presse à paille • Moissonneuse • Épandeur

|                    |              |
|--------------------|--------------|
| Version            | STANDARD     |
| Type               | TL           |
| Tyre Size          | 500/50 - 17  |
| LI/SS DRIVE WHEEL  | 145 A8/141 B |
| LI/SS FREE ROLLING | 157 A8/154 B |

## Dimensions International Standard

|                            |                |
|----------------------------|----------------|
| Ply Rating                 | 18             |
| Section Width (mm)         | 510            |
| Overall Diameter (mm)      | 945            |
| Static Loaded Radius (mm)  | 416            |
| Rolling Circumference (mm) | 2750           |
| Rim Rec                    | 16.00          |
| ECE                        | E4-106R-002305 |

## Load capacity (Kg)

| km/h / bar | 3.80 | 3.90 | 4.00 |
|------------|------|------|------|
| 10 FR      | 5605 | 5690 | 5775 |
| 20 FR      | 5045 | 5120 | 5200 |
| 30 FR      | 4485 | 4555 | 4620 |
| 40 FR      | 4005 | 4065 | 4125 |
| 50 FR      | 3605 | 3660 | 3750 |
| 10 DW      | 3940 | 3995 | 4060 |
| 20 DW      | 3545 | 3595 | 3655 |
| 30 DW      | 3155 | 3200 | 3250 |
| 40 DW      | 2815 | 2855 | 2900 |
| 50 DW      | 2535 | 2570 | 2575 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 14:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..