

FLOTATION TR 678 - Fiche de données



Description

FLOTATION TR 678 a été particulièrement conçu pour l'outillage agricole et les remorques tant sur route que hors route. Il permet de transporter des charges lourdes à de basses pressions, tout en assurant un moindre compactage du sol. Ce pneu garantit une traction exceptionnelle et possède d'excellentes qualités d'autonettoyage.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole • Remorque

SIZE	Version	USACode	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
320/60 - 12	STANDARD	94067282		120 A8	132 A8		10.50 I		12.9	27.1	12.9	83.1	TT	E11-106R-006617
280/60 - 15.5	STANDARD	94050154	128 A8				8.0		10.8	29.5	14.1	88.6	TL	E11-106R-004262
280/60 - 15.5	STANDARD	94019922	115 A8				8.0		10.8	29.5	14.1	88.6	TL	E11-106R-004261
500/45 - 20	STANDARD	94068906		148 A8	160 A8		16.00 DC		19.5	38.6	0	0	TL	E11-106R-006816
600/40 - 22.5	DUAL BEAD	94051915		157 A8	169 A8	20	AG 20.00		24.2	42.7	19	128.5	TL	E11-106R-006501
600/40 - 22.5	DUAL BEAD HD	94054152		157 A8	169 A8	20	AG 20.00		24.2	42.7	19	128.5	TL	E11-106R-004619
600/40 - 22.5	INDUSTRIAL	94051915		157 A8	169 A8	20	AG 20.00		24.2	42.7	19	128.5	TL	
650/45 - 22.5	STANDARD	94026517	166 B			20	AG 20.00		25.6	45.3	19.8	130	TL	E11-106R-004400
650/45 - 22.5	STANDARD	94005420	160 D				AG 20.00		25.6	45.3	19.8	130	TL	E11-106R-004399
650/45 - 22.5	STEEL BELTED	94030170	166 B			20	AG 20.00		25.6	45.3	19.8	130	TL	E11-106R-004401
710/40 - 22.5	ARAMID + STEEL BELTED	94064755	173 A8				AG 24.00		27.8	45.9	0	0	TL	E11-106R-006011
710/40 - 22.5	STEEL BELTED	94064755	173 A8				AG 24.00		27.8	45.9	21.5	142.7	TL	E11-106R-006011

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 12:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..