

JUMBO TRAX HD - Fiche de données



Description

JUMBO TRAX HD est un pneu avec dessin à blocs de la bande de roulement pour les chargeuses compactes. Ce pneu se distingue de par son extraordinaire résistance aux coupures et déchirures et il est particulièrement indiqué pour les services pénibles. La bande de roulement profonde associée à l'excellente protection des flancs garantit un long cycle de vie du pneu. JUMBO TRAX HD est aussi disponible en version spéciale.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Chargeur compact

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10 - 16.5	IMPLEMENT	94057313	120 A8	10	8.25		10.6	31.3	14.3	92.3	TL	E11-106R-003523
10 - 16.5	SPECIAL	94031863		10	8.25		10.6	31.3	14.3	92.3	TL	
10 - 16.5	STANDARD	94017287		10	8.25		10.6	31.3	14.3	92.3	TL	
12 - 16.5	STANDARD	94017294		10	9.75		12.8	33.7	15.2	99.3	TL	E11-106R-005563
12 - 16.5	STANDARD	94029549		12	9.75		12.8	33.7	15.2	99.3	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..