

LG RIB - Spécifications techniques



Description

LG RIB est un pneu pour pelouses et jardins, approprié pour les faucheuses et les micro tracteurs. Le dessin spécifique de la bande de roulement rend le pneu délicat sur le terrain, pour éviter d'abîmer la pelouse et faciliter le maniement et les manœuvres. LG RIB est disponible dans une version "aramid belted", avec ceintures en aramide, pour les utilisateurs qui ont besoin d'une plus grande résistance aux perforations.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Faucheuse • Micro tracteur

| | |
|-----------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 15 X 6.00 - 6 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94012954 |
| Ply Rating | 4 |
| Section Width (inch) | 6 |
| Overall Diameter (inch) | 14.4 |
| Static Loaded Radius (inch) | 6.3 |
| Rolling Circumference (inch) | 41.7 |
| Rim Rec | 4.50 A |
| ECE | E11-106R-003466 |

Load capacity (lbs)

| | |
|-----------|-----|
| mph / psi | 30 |
| 10 | 565 |

Printed on 02/07/2024 18:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..