

LG RIB - Fiche de données



Description

LG RIB est un pneu pour pelouses et jardins, approprié pour les faucheuses et les micro tracteurs. Le dessin spécifique de la bande de roulement rend le pneu délicat sur le terrain, pour éviter d'abîmer la pelouse et faciliter le maniement et les manœuvres. LG RIB est disponible dans une version "aramid belted", avec ceintures en aramide, pour les utilisateurs qui ont besoin d'une plus grande résistance aux perforations.

UM

US Standard

Construction

BIAS

Machinery

Agriculture: Faucheuse • Micro tracteur

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
11 X 4.00 - 5	STANDARD	94074686	39 A6	4	3.00 A		4.1	10.7	0	0	TL	E11-106R-008779
13 X 5.00 - 6	ARAMID BELTED	94013012		6	3.50 A		5	12.8	5.7	37.1	TL	E11-106R-005221
13 X 5.00 - 6	STANDARD	94012930		4	3.50 A		5	12.8	5.7	37.1	TL	E11-106R-003465
15 X 6.00 - 6	ARAMID BELTED	94013029		6	4.50 A		6	14.4	6.3	41.7	TL	E11-106R-003504
15 X 6.00 - 6	STANDARD	94012954		4	4.50 A		6	14.4	6.3	41.7	TL	E11-106R-003466
15 X 6.00 - 6	STANDARD	94012961		6	4.50 A		6	14.4	6.3	41.7	TL	E4-106R-002173
16 X 6.50 - 8	ARAMID BELTED	94052165		10	5.375 I - 55; I - 70; I - 90		6.7	16.1	7.2	46.6	TL	E11-106R-005404
16 X 6.50 - 8	ARAMID BELTED	94013036		6	5.375 I - 55; I - 70; I - 90		6.7	16.1	7.2	46.6	TL	E11-106R-003499
16 X 6.50 - 8	STANDARD	94041701		8	5.375 I - 55; I - 70; I - 90		6.7	16.1	7.2	46.6	TL	
16 X 6.50 - 8	STANDARD	94030866		10	5.375 I - 55; I - 70; I - 90		6.7	16.1	7.2	46.6	TL	E4-106R-003372
16 X 6.50 - 8	STANDARD	94012978		4	5.375 I - 55; I - 70; I - 90		6.7	16.1	7.2	46.6	TT	E11-106R-003467
16 X 6.50 - 8	STANDARD	94012985		4	5.375 I - 55; I - 70; I - 90		6.7	16.1	7.2	46.6	TL	E11-106R-003467
16 X 6.50 - 8	STANDARD	94013005		6	5.375 I - 55; I - 70; I - 90		6.7	16.1	7.2	46.6	TL	E11-106R-003468
20 X 10.00 - 10	STANDARD	94026128		4	8.00 I - 55; I - 70; I - 90	7.00 I - 55; I - 70; I - 90	9.3	19.6	8.7	56.9	TL	E11-106R-003469

Printed on 02/07/2024 18:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..