

LG SMOOTH - Spécifications techniques



Description

LG SMOOTH est un pneu pour pelouses et jardins, approprié pour les tondeuses. Bien qu'il soit délicat sur le terrain, le pneu présente un dessin à l'avant-garde qui lui assure une durée de vie plus longue et facilite le maniement et les manœuvres. LG SMOOTH est disponible dans une version "aramid belted", avec ceintures en aramide, pour les utilisateurs qui ont besoin d'une plus grande résistance aux perforations.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Faucheuse • Micro tracteur

Version	STANDARD
Type	TL
Tyre Size	20 X 10.00 - 10

Dimensions US Standard

Usa code	94025664
Ply Rating	2
Section Width (inch)	9.6
Overall Diameter (inch)	19.7
Static Loaded Radius (inch)	8.8
Rolling Circumference (inch)	57.1
Rim Rec	8.00 I - 55
Rim Alt	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-005201

Load capacity (lbs)

mph / psi	10
10	740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 12:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..