

## LIFT STAR PLUS - Spécifications techniques



### Description

LIFT STAR PLUS est un pneu diagonal particulièrement conçu pour les chargeuses télescopiques utilisées pour les opérations pénibles dans le secteur du bâtiment et dans d'autres applications difficiles. Le profil bas du flanc offre une excellente stabilité lors des opérations de levage en hauteur, tandis que le dessin non directionnel de la bande de roulement permet une plus grande polyvalence lors du montage. De plus, le flanc a été particulièrement conçu pour assurer une résistance encore plus grande aux coupures et lacérations.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industriel: Chargeuse télescopique

Version	STANDARD
Type	TL
Tyre Size	370/75 - 28

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	365
Overall Diameter (mm)	1270
Static Loaded Radius (mm)	583
Rolling Circumference (mm)	3851
Rim Rec	11.00
ECE	E11-106R-005331

## Load capacity (Kg)

km/h / bar	3.25	5.00
50	3250	-
10	-	5450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 23:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..