

## LP 450 - Fiche de données



### Description

LP 450 est un pneu pour une utilisation essentiellement sur route avec des remorques à plateau surbaissé dans les applications de transport. Ce pneu haute vitesse permet de réaliser d'importantes économies de carburant et il bénéficie d'un long cycle de vie.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriel: Remorque surbaissé

| SIZE     | Version  | USACode  | PR | RIM REC | RIM ALT | SW  | OD | SLR  | RC   | Type |
|----------|----------|----------|----|---------|---------|-----|----|------|------|------|
| 8 - 14.5 | STANDARD | 94008315 | 12 | 6.00 MH |         | 8.4 | 28 | 12.6 | 83   | TL   |
| 9 - 14.5 | STANDARD | 94031306 | 14 | 7.00 MH |         | 9.7 | 28 | 12.7 | 83.3 | TL   |
| 9 - 14.5 | STANDARD | 94008322 | 12 | 7.00 MH |         | 9.7 | 28 | 12.7 | 83.3 | TL   |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..