

MINEFORCE - Fiche de données



Description

MINEFORCE est un pneu à carcasse radiale spécialement conçu pour les camions de transport dans les exploitations minières et les carrières. Le pneu haute performance pour camion de transport MINEFORCE est la réponse innovante de BKT aux environnements miniers rocheux, abrasifs et difficiles. Il est doté d'une bande de roulement unique avec des composés spéciaux spécialement développés pour le travail dans des environnements miniers durs, rocheux et difficiles. Sa large surface de contact avec des pattes rigides assure une usure uniforme de la bande de roulement et un cycle de vie plus long.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Tombereau rigide

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
24.00 - 35	CUT RESISTANT	94069033	E4	48	17.00/3.5		25.8	86.2	39.5	255.2	TL	253
27.00 - 49	STANDARD	94070107	E4	48	19.50/4.0		29.1	106.1	49.3	314.4	TL	325
27.00 - 49	STANDARD	94069064	E4	54	19.50/4.0		29.1	106.1	49.3	314.4	TL	325

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..