

MUD POWER HD - Spécifications techniques



Description

MUD POWER HD a été spécialement conçu pour les chargeuses compactes. Le dessin profond de la bande de roulement, en plus de la disposition spéciale des pavés, assure une excellente traction sur terrains meubles et mouillés. MUD POWER HD a été réalisé avec un mélange industriel spécial et se distingue par une robuste carcasse en nylon qui permettent d'avoir un cycle de vie plus long du pneu même dans des conditions pénibles.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chargeur compact

Version	STANDARD
Type	TL
Tyre Size	10 - 16.5

Dimensions International Standard

Ply Rating	10
Section Width (mm)	268
Overall Diameter (mm)	800
Rim Rec	8.25
TRA Code	R4

Load capacity (Kg)

	km/h / bar	5.20
	10	2135
	15	1685
	25	1560

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 00:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..