

## MULTIMAX MP 522 - Spécifications techniques



### Description

MULTIMAX MP 522 est le pneu polyvalent de BKT conçu pour de nombreux domaines d'application dans le secteur agro-industriel. Il est adapté pour toutes les opérations de levage et chargement sur véhicules tels que les chargeurs télescopiques et chargeuses compactes. Stabilité et traction sont ses atouts, associés à une excellente résistance aux crevaisons. Grâce au mélange particulier, MULTIMAX MP 522 garantit une résistance aux coupures et déchirures exceptionnelle.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Chargeuse compacte • Chargeuse télescopique

Industriel: Chargeuse compacte • Chargeuse télescopique

|           |                 |
|-----------|-----------------|
| Version   | STANDARD        |
| Type      | TL              |
| Tyre Size | 400/70 R 24 IND |
| LI/SS     | 152 A8/B        |

## Dimensions International Standard

|                            |  |
|----------------------------|--|
| Section Width (mm)         | 404  |
| Overall Diameter (mm)      | 1170                                       |
| Static Loaded Radius (mm)  | 533  |
| Rolling Circumference (mm) | 3527                                       |
| SRI (mm)                   | 575  |
| Rim Rec                    | 13   |
| Rim Alt                    | DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L |
| ECE                        | E11-106R-002964                            |

## Load capacity (Kg)

| km/h / bar | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.5  | 4.0  | 4.2  | 4.4  |
|------------|------|------|------|------|------|------|------|------|------|
| 50         | 1705 | 2025 | 2310 | 2630 | 2950 | 3160 | 3550 | -    | -    |
| 40         | 1705 | 2025 | 2310 | 2630 | 2950 | 3160 | 3550 | -    | -    |
| 30         | 1825 | 2170 | 2470 | 2815 | 3155 | 3385 | 3800 | -    | -    |
| 25         | 1895 | 2250 | 2565 | 2920 | 3275 | 3515 | 3945 | -    | -    |
| 10 Cyc.    | 2080 | 2560 | 3010 | 3465 | 3945 | 4290 | 4850 | 5115 | 5325 |
| Static     | 3185 | 3920 | 4615 | 5310 | 6045 | 6575 | 7435 | 7840 | 8165 |

Printed on 04/07/2024 06:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..