

MULTIMAX MP 522 - Spécifications techniques



Description

MULTIMAX MP 522 est le pneu polyvalent de BKT conçu pour de nombreux domaines d'application dans le secteur agro-industriel. Il est adapté pour toutes les opérations de levage et chargement sur véhicules tels que les chargeurs télescopiques et chargeuses compactes. Stabilité et traction sont ses atouts, associés à une excellente résistance aux crevaisons. Grâce au mélange particulier, MULTIMAX MP 522 garantit une résistance aux coupures et déchirures exceptionnelle.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Chargeuse compacte • Chargeuse télescopique

Industriel: Chargeuse compacte • Chargeuse télescopique

Version	STANDARD
Type	TL
Tyre Size	400/80 R 24 IND (16.0/80 R 24)
LI/SS	162 A8/B

Dimensions International Standard

Section Width (mm)	404
Overall Diameter (mm)	1250
Static Loaded Radius (mm)	553
Rolling Circumference (mm)	3778
SRI (mm)	600
Rim Rec	DW 13
Rim Alt	DW 12 ; DW 13 L ; DW 14 L
ECE	E11-106R-002965

Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.4	3.6	4.0	4.4	4.6	4.8	5.0	5.2	5.4
50	1855	2185	2565	2900	3230	3350	3520	3895	4220	4435	4540	4750	-	-
40	1855	2185	2565	2900	3230	3350	3520	3895	4220	4435	4540	4750	-	-
30	1985	2340	2750	3105	3460	3590	3770	4170	4515	4745	4860	5085	-	-
25	2060	2430	2850	3220	3590	3725	3910	4330	4690	4925	5040	5275	-	-
10 Cyc.	2280	2785	3280	3850	4350	4600	4845	5280	5845	6090	6330	6655	6810	7125
Static	3500	4270	5030	5900	6670	7050	7430	8100	8960	9340	9710	10205	10445	10925

Printed on 04/07/2024 06:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..