

MULTIMAX MP 525 - Spécifications techniques



Description

MULTIMAX MP 525 est un pneu radial polyvalent All Steel (tout acier) conçu pour les véhicules universels, les chargeuses télescopiques, les chargeuses compactes et les niveleuses dans les applications agro-industrielles. Ce pneu a été spécialement développé pour transporter de charges lourdes à des vitesses plus élevées sur route et hors route. En effet, le dessin large non directionnel de la bande de roulement offre une traction exceptionnelle sur n'importe quelle surface en plus d'excellentes propriétés autonettoyantes. Le flanc robuste assure une stabilité latérale exceptionnelle en mode de levage, ce qui en fait le choix idéal pour les opérations agricoles et de manutention de matériaux. MULTIMAX MP 525 est réalisé avec un mélange spécial de la bande de roulement résistant aux coupures et déchirures, qui garantit une plus longue durée de vie du pneu grâce à son extraordinaire résistance à tous les types de coupures et de crevaisons.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Chargeuse télescopique • Véhicule universel
Industriel: Chargeuse compacte • Niveleuse • Chargeuse télescopique

Version	STANDARD
Type	TL
Tyre Size	405/70 R 20 (16.0/70 R 20)
LI/SS	152 J/168 A2

Dimensions International Standard

Overall Width (mm)	405
Overall Diameter (mm)	1076
Static Loaded Radius (mm)	482
Rolling Circumference (mm)	3260
Rim Rec	13
Rim Alt	12; 13 SDC
ECE	E11-54R-0020576

Load capacity (Kg)

km/h / bar	6.00
100	3550
10	5600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 11:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..