

## MULTIMAX MP 527 - Fiche de données



### Description

MULTIMAX MP 527 est un pneu radial polyvalent pour chargeurs télescopiques et chargeuses compactes dans les applications agro-industrielles. Ce pneu présente un dessin à blocs de la bande de roulement qui garantit une excellente traction même sur les surfaces dures. Le flanc robuste du pneu assure une stabilité exceptionnelle en mode levage. MULTIMAX MP 527 est réalisé avec un mélange particulièrement résistant aux coupures et déchirures, ce qui se traduit par une longue vie du pneu.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Chargeuse compacte • Chargeuse télescopique

Industriel: Chargeuse compacte • Chargeuse télescopique

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
<b>340/80 R 18 IND</b>	STANDARD	94048694	143 A8/B	11; 11 SDC; W 11	W 10; 12; 12 SDC	13.5	39.4	17.9	119.2	TL	E4-106R-002981
<b>360/70 R 18 IND</b>	STANDARD	94053650	142 A8/B	11	W10; 11 SDC; W11; 12; 12 SDC	14.2	38.1	17.3	113.7	TL	E11-106R-002996
<b>340/80 R 20 IND</b>	STANDARD	94053452	144 A8/B	11	W10; 11 SDC; W11; 12; 12 SDC	13.5	41.4	19	125	TL	E11-106R-003957
<b>400/70 R 20 IND (16.0/70 R 20)</b>	STANDARD	94052073	149 A8/B	13	12 SDC; 13 SDC; 14	15.9	42	19.4	129.2	TL	E4-106R-002656
<b>400/70 R 24 IND</b>	STANDARD	94053483	152 A8/B	13	DW 12; DW 13; DW 13 L; 13 SDC; DW 14 L	15.9	46.1	21.3	141.6	TL	E11-106R-003958
<b>400/80 R 24 IND</b>	STANDARD	94052226	162 A8/B	DW 13	DW 12; DW 13 L; DW 14 L	15.9	49.2	22.8	150.9	TL	E11-106R-002982
<b>440/80 R 24 IND</b>	STANDARD	94052080	161 A8/B	DW 14 L	DW 13; DW 13 L; DW 15 L	17.4	51.7	23.7	156.9	TL	E4-106R-002657
<b>460/70 R 24 IND (17.5L R 24)</b>	STANDARD	94052097	159 A8/B	DW 15 L	DW 14 L; DW 16 L	18.3	49.4	22.6	149.6	TL	E11-106R-002983
<b>500/70 R 24 IND</b>	STANDARD	94052233	164 A8/B	DW 16 L	DW 15 L; DW 18 L	19.8	51.6	23.5	158.2	TL	E4-106R-002658
<b>480/80 R 26 IND</b>	STANDARD	94055012	160 A8/B	DW 15 L	DW 16 L	18.9	56.2	25.3	167.7	TL	E11-106R-004069
<b>440/80 R 28 IND</b>	STANDARD	94052714	156 A8/B	DW 14 L	DW 13; DW 13 L; DW 15 L	17.4	55.7	25.5	168.1	TL	E11-106R-002984

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 17:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..