

## MULTIMAX SR 261 - Spécifications techniques



### Description

Le MULTIMAX SR 261 est un pneu radial tout en acier avec des ceintures en acier multicouches spécialement conçu pour les remorques à plateau surbaissé, les remorques agricoles et les grues mobiles portuaires dans le cadre d'applications de transport et d'opérations portuaires. Sa carcasse robuste et son composé de bande de roulement spécial sont la garantie d'une plus longue durée de vie. Grâce à la conception de la bande de roulement lamellisée, le MULTIMAX SR 261 offre une traction optimale quelle que soit l'application. De plus, la conception unique de la bande de roulement 5 RIB maximise le contact avec le sol pour une usure uniforme de cette dernière.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industriel: Remorque surbaissé • Grue automotrice

Version	STANDARD
Type	TL
Tyre Size	215/75 R 17.5
LI/SS	135/133 J

## Dimensions US Standard

Usa code	94071067
Overall Width (inch)	8.3
Overall Diameter (inch)	30.5
Static Loaded Radius (inch)	14
Rolling Circumference (inch)	93.3
Rim Rec	6.00
Rim Alt	6.75

## Load capacity (lbs)

	mph / psi	125
	62 Load Single	4805
	62 Load Dual	4540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 00:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..